

METROFLOR LVT

Flexible LVT by METROFLOR™

ENVIRONMENTAL DATA SHEET LOOSE LAY COLLECTIONS

Metroflor® is not just the name of an HMTX Industries company, but the essence of revolution in resilient flooring. As the leader in sustainability and transparency, we are engaging in collaborative partnerships that result in healthy, high-performing and biophilically-designed products. Disruptive intelligence dictates our culture. We are answering the need to educate, motivate, and encourage individuals to invest in a restorative ecosystem.

The future starts with all of us.

DECLARATIONS & CERTIFICATIONS

HEALTH PRODUCT DECLARATION® (HPD)	Available at www.mindfulmaterials.com
DECLARE™ LABEL	Available at www.mindfulmaterials.com
JUST™ LABEL - CORPORATE	Label #HMT-003 Available at www.metroflor.com
FloorScore®	Certificate #SCS-FS-01967 Available at www.metroflor.com
CALIFORNIA PROP 65	Compliant
CDPH v1.2 - 2017	Compliant
REACH SVHC	Compliant (REACH SVHC 205)

PRODUCT ATTRIBUTES

PRE-CONSUMER RECYCLED CONTENT	None
POST-CONSUMER RECYCLED CONTENT	None
STABILIZERS	No Red List Heavy Metals
PHthalATES	Phthalate-Free
FORMALDEHYDE	Formaldehyde-Free
FLAME RETARDANTS	None
ANTIMICROBIAL CHEMICALS	Octhilinone, 2-n-octyl-4-isothiazolin-3-one (OIT)

PRODUCT SAFETY & TRANSPARENCY

Metroflor's product testing program is remarkably stringent. Metroflor products are tested to the latest standards for Volatile Organic Compounds (VOCs), formaldehyde, phthalates, and heavy metals. In fact, the standards used for the testing of phthalates and heavy metals in Metroflor LVT™ are the same standards used for the testing of children's toys, setting a very high bar. Metroflor LVT Loose Lay has surpassed that bar – and we welcome you to inspect our HPD and Declare Label to your satisfaction. Equally important is the fact that Metroflor LVT is FloorScore certified, thus ensuring it meets strict standards for indoor air quality.

By selecting Metroflor, you have made the choice for safe and sustainable products. And isn't that what we all want when it comes to products in our businesses and homes? Come join us at Metroflor and discover all of the possibilities of resilient flooring.

AFFILIATIONS



Metroflor LVT - Over The Top: Chalk

METROFLOR LVT

Flexible LVT by METROFLOR™

ENVIRONMENTAL DATA SHEET LOOSE LAY COLLECTIONS

WELL BUILDING STANDARD V2 - CONTRIBUTIONS TOWARDS CERTIFICATION

CONCEPT	FEATURE	PART	COMMENTS
Materials	X01 - Material Restrictions	Part 1(a): Restrict Asbestos	Metroflor LVT does not contain asbestos and thus complies with this prerequisite for resilient flooring.
	X05 - Enhanced Material Restrictions	Part 2(a): Select Compliant Architectural and Interior Products	Metroflor LVT does not contain flame retardants, PFAs, or orthophthalates.
	X06 - VOC Restrictions	Part 1(a)(b): Limit VOCs from Wet-Applied Products	Prevail® 6000 PSA, the adhesive required for use with Metroflor LVT Loose Lay when glue-down installations are necessary, is FloorScore certified and thus meets the requirements of SCAQMD Rule 1168 and CDPH Standard Method v1.2-2017.
		Part 2(a): Restrict VOC Emissions from Furniture, Architectural and Interior Products	Metroflor LVT is FloorScore certified and thus meets the requirements of CDPH Standard Method v1.2-2017.
	X07 - Materials Transparency	Part 1(a)(b): Select Products with Disclosed Ingredients	Material ingredients for Metroflor LVT Loose Lay have been disclosed in the form of a Declare Label and an HPD.
		Part 2(a)(b): Select Products with Enhanced Ingredient Disclosure	All material ingredients at/above 100ppm in Metroflor LVT Loose Lay have been disclosed in the form of a Declare Label and an HPD.
	X08 - Materials Optimization	Part 1: Select Materials with Enhanced Chemical Restrictions	Option 1(b)(3): Metroflor LVT does not contain any ingredients on the REACH SVHC list.

LEED V4.1 - CONTRIBUTIONS TOWARDS CERTIFICATION

CATEGORY	PREREQ/CREDIT	DESCRIPTION	COMMENTS
Material & Resources	MR Credit	Building Product Disclosure and Optimization - Material Ingredients (Option 1)	Material ingredients for Metroflor LVT Loose Lay have been disclosed in the form of a Declare Label and a Health Product Declaration (HPD).
Indoor Environmental Quality	EQ Credit	Low-Emitting Materials: Adhesives & Sealants	Prevail 6000 PSA, the adhesive required for use with Metroflor LVT Loose Lay when glue-down installations are necessary, is FloorScore certified.
		Low-Emitting Materials: Flooring	Metroflor LVT is FloorScore certified and thus meets the requirements of CDPH Standard Method v1.2-2017.



Metroflor LVT - Over The Top: Mist Grey