

# METROFLOR LVT

Flexible LVT by METROFLOR™

## OVER THE TOP - LOOSE LAY TECHNICAL DATA SHEET

### PHYSICAL PROPERTIES & PACKAGING - PLANK (LOOSE LAY SOLID VINYL TILE FLOORING - 5.0 MM / 0.5 MM)

COLLECTIONS	Oak Framing, Fleur De Lis	Clean Oak, San Marcos Oak
USE	Commercial & Residential ( <i>Refer to the Recommended Use PDF for Recommended Commercial Areas</i> )	
SIZE	7 x 48 in. (177.8 x 1,219.2 mm)	9 x 60 in. (228.6 x 1,524 mm)
THICKNESS - LVT	5.0 mm (0.197 in.)	5.0 mm (0.197 in.)
THICKNESS - WEAR LAYER	0.5 mm (20 mil)	0.5 mm (20 mil)
PROFILE	Micro-Bevel Edge	Micro-Bevel Edge
FINISH	FX3 Surface Protectant with Ultra-Fresh	FX3 Surface Protectant with Ultra-Fresh
EMBOSS	Oak Framing - Natural Timber Fleur De Lis - Coral	Clean Oak - In-Register San Marcos Oak - In-Register
COVERAGE - CARTON	8 Pieces/Carton (18.7 Sq.Ft. / 1.73 Sq.M.)	5 Pieces/Carton (18.8 Sq.Ft. / 1.74 Sq.M.)
COVERAGE - PALLET	50 Cartons/Pallet (933 Sq.Ft. / 86.7 Sq.M.)	52 Cartons/Pallet (975 Sq.Ft. / 90.6 Sq.M.)
COVERAGE - CONTAINER	20 Pallets/Container (18,667 Sq.Ft. / 1,734 Sq.M.)	20 Pallets/Container (19,500 Sq.Ft. / 1,812 Sq.M.)
LIMITED WARRANTY	15-Year Commercial / Lifetime Residential	15-Year Commercial / Lifetime Residential

### PHYSICAL PROPERTIES & PACKAGING - TILE (LOOSE LAY SOLID VINYL TILE FLOORING - 5.0 MM / 0.5 MM)

COLLECTIONS	Belgium Weave	Smooth Concrete
USE	Commercial & Residential ( <i>Refer to the Recommended Use PDF for Recommended Commercial Areas</i> )	
SIZE	16 x 32 in. (406.4 x 812.8 mm)	24 x 24 in. (609.6 x 609.6 mm)
THICKNESS - LVT	5.0 mm (0.197 in.)	5.0 mm (0.197 in.)
THICKNESS - WEAR LAYER	0.5 mm (20 mil)	0.5 mm (20 mil)
PROFILE	Square Edge	Micro-Bevel Edge
FINISH	FX3 Surface Protectant with Ultra-Fresh	FX3 Surface Protectant with Ultra-Fresh
EMBOSS	Linen	Rough Concrete
COVERAGE - CARTON	4 Pieces/Carton (14.2 Sq.Ft. / 1.32 Sq.M.)	4 Pieces/Carton (16 Sq.Ft. / 1.49 Sq.M.)
COVERAGE - PALLET	68 Cartons/Pallet (967 Sq.Ft. / 89.8 Sq.M.)	60 Cartons/Pallet (960 Sq.Ft. / 89.2 Sq.M.)
COVERAGE - CONTAINER	20 Pallets/Container (19,342 Sq.Ft. / 1,797 Sq.M.)	20 Pallets/Container (19,200 Sq.Ft. / 1,784 Sq.M.)
LIMITED WARRANTY	15-Year Commercial / Lifetime Residential	15-Year Commercial / Lifetime Residential

# METROFLOR LVT

Flexible LVT by METROFLOR™

## OVER THE TOP - LOOSE LAY TECHNICAL DATA SHEET

### STANDARDS — MANUFACTURING & USAGE (ASTM F1700)

STANDARD	DESCRIPTION	REQUIREMENTS	RESULTS
ASTM F1700	Classification	Refer to Standard	Class III, Type B
ASTM F1700	Physical Characteristics / Tolerances	Refer to Standard	Passes Requirements <sup>1</sup>
ASTM F1914	Residual Indentation	Average: < 8%, Any Sample ≤ 10%	Passes Requirements
ASTM F137	Flexibility	No Crack or Break, 1-in. (25.4 mm) Mandrel	Passes Requirements
ASTM F2199	Dimensional Stability	≤ 0.020 in./lin. ft (0.51 mm/305 mm)	Passes Requirements
ASTM F925	Chemical Resistance	No More Than "Slight Change"	Passes Requirements
ASTM F1514	Resistance to Heat	Average ΔE < 8.0	Passes Requirements
ASTM F1515	Resistance to Light	Average ΔE < 8.0	Passes Requirements

### STANDARDS — SAFETY & PERFORMANCE

STANDARD	DESCRIPTION	REQUIREMENTS	RESULTS
ASTM E648	Critical Radiant Flux (Radiant Panel)	Class I: ≥ 0.45 W/Sq. cm.	Passes Requirements <sup>2</sup>
ASTM E662	Smoke Density	Flaming & Non-Flaming ≤ 450	Passes Requirements <sup>3</sup>
CDPH Standard Method v1.2	VOCs/TVOCs, Formaldehyde	Refer to Standard	Passes Requirements
REACH SVHC 205	Substances of Very High Concern	Per Substance: ≤ 0.1% w/w weight/weight)	Passes Requirements
ASTM F963	Heavy Metals	Refer to Standard (Table 1)	Passes Requirements
CPSC-CH-C1001-09.3	Phthalates	Per CPSIA <sup>4</sup> ≤ 0.1% per Substance	Passes Requirements
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A (No Official Requirements)	≥ 0.6 (Dry)
ANSI ESD STM97.2	Body Voltage	N/A (No Official Requirements)	Average (Abs) ≤ 2.0kV
ASTM F970	Static Load	N/A (No Official Requirements)	0.005 in., 1,000 psi

### STANDARDS — SOUND

ASSEMBLY	ASTM E90	ASTM E492	ASTM E2179	RESULTS
6" Concrete Slab + Drop-Ceiling	STC 61	IIC 60	Not Applicable	Tested assemblies pass International Building Code (IBC) requirements of STC ≥ 50 and IIC ≥ 50 for multi-story dwellings

### NOTES

- (1) ASTM F1700 - Physical Characteristics / Tolerances: includes Size, Squareness, Thickness, and Wear Layer Thickness (Commercial Class).
- (2) ASTM E648 - Critical Radiant Flux (Radiant Panel): Passes Requirements for Class I per International Building Code (IBC) 2018 & NFPA 101 Life Safety Code.
- (3) ASTM E662 - Smoke Density: 450 is the limit established by many state, county, and/or local building and/or fire codes, but is not set as a limit for (resilient) flooring products nationwide. Thus, Smoke Density requirements for flooring products may vary from jurisdiction to jurisdiction. Consult your building inspector / fire marshal to learn more.
- (4) CPSIA = Consumer Product Safety Improvement Act.

Ultra-Fresh is a registered trademark of Thomson Research Associates, Inc.